KitchenAid®

GAS FREESTANDING RANGES AND VENTILATION PAIRING GUIDE

GAS FREESTANDING RANGES

	30” REAR CONTROL			30” FRONT CONTROL			
	KFGG500E	KFGD500E	KFDD500ESS	KSGG700E	KSGB900E	YKSDB900ESS	KSDG950ESS
UNDER CABINET HOODS							
30” - **KVUB400GSS**	✓	✓	✓	✓	✓	✓	✓
36” - **KVUB406GSS**	×	×	×	×	×	×	×
30” - **KVUB600DSS**	✓	✓	✓	✓	✓	✓	✓
36” - **KVUB606DSS**	×	×	×	×	×	×	×
30” - **KXU2830JSS**	✓	✓	✓	✓	✓	✓	✓
36” - **KXU2836JSS**	×	×	×	×	×	×	×
WALL MOUNT AND ISLAND MOUNT HOODS							
30” - **KVWB400DSS**	✓	✓	✓	✓	✓	✓	✓
36” - **KVWB406DSS**	×	×	×	×	×	×	×
30” - **KVWB600HBS**	✓	✓	✓	✓	✓	✓	✓
36” - **KVWB606HBS**	×	×	×	×	×	×	×
36” - **KVIB606DSS**	×	×	×	×	×	×	×
PRO STYLE VENTILATION AND LINERS							
30” - **KVUC600KSS**	✓	✓	✓	✓	✓	✓	✓
36” - **KVUC606KSS**	×	×	×	×	×	×	×
36” - **KVWC906KSS**	×	×	×	×	×	×	×
48” - **KVWC908KSS**	×	×	×	×	×	×	×
36” - **KVWC956KSS**	×	×	×	×	×	×	×
48” - **KVWC958KSS**	×	×	×	×	×	×	×
30” - **UVL5430JSS**	✓	✓	✓	✓	✓	✓	✓
36” - **UVL6036JSS***	×	×	×	×	×	×	×
48” - **UVL6048JSS***	×	×	×	×	×	×	×

*** Custom hood liners can be used with any of the following blower motors:**
UXB1170**KYS** (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0585**KYS** (585 CFM)

**** Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer’s responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

IMPORTANT: Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

KitchenAid®

ELECTRIC FREESTANDING RANGES AND VENTILATION PAIRING GUIDE

ELECTRIC FREESTANDING RANGES

	30” REAR CONTROL				30” FRONT CONTROL			
	YKFEG500E	YKFEG510ESS	YKFED500ESS	YKFID500ESS	YKSEG700E	YKSEB900E	KSEG950ESS	KSIB900ESS
UNDER CABINET HOODS								
30” - **KVUB400GSS**	✓	✓	✓	✓	✓	✓	✓	✓
36” - **KVUB406GSS**	×	×	×	×	×	×	×	×
30” - **KVUB600DSS**	✓	✓	✓	✓	✓	✓	✓	✓
36” - **KVUB606DSS**	×	×	×	×	×	×	×	×
30” - **KXU2830JSS**	✓	✓	✓	✓	✓	✓	✓	✓
36” - **KXU2836JSS**	×	×	×	×	×	×	×	×
WALL MOUNT AND ISLAND MOUNT HOODS								
30” - **KVWB400DSS**	✓	✓	✓	✓	✓	✓	✓	✓
36” - **KVWB406DSS**	×	×	×	×	×	×	×	×
30” - **KVWB600HBS**	✓	✓	✓	✓	✓	✓	✓	✓
36” - **KVWB606HBS**	×	×	×	×	×	×	×	×
36” - **KVIB606DSS**	×	×	×	×	×	×	×	×
PRO STYLE VENTILATION AND LINERS								
30” - **KVUC600KSS**	✓	✓	✓	✓	✓	✓	✓	✓
36” - **KVUC606KSS**	×	×	×	×	×	×	×	×
36” - **KVWC906KSS**	×	×	×	×	×	×	×	×
48” - **KVWC908KSS**	×	×	×	×	×	×	×	×
36” - **KVWC956KSS**	×	×	×	×	×	×	×	×
48” - **KVWC958KSS**	×	×	×	×	×	×	×	×
30” - **UVL5430JSS**	✓	✓	✓	✓	✓	✓	✓	✓
36” - **UVL6036JSS***	×	×	×	×	×	×	×	×
48” - **UVL6048JSS***	×	×	×	×	×	×	×	×

*** Custom hood liners can be used with any of the following blower motors:**
UXB1170KYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0585KYS (585 CFM)

**** Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer’s responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

IMPORTANT: Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

KitchenAid®

COMMERCIAL STYLE RANGES / RANGETOPS AND VENTILATION PAIRING GUIDE

RANGES AND RANGETOPS

	30” COMMERCIAL STYLE RANGES / RANGETOPS			36” COMMERCIAL STYLE RANGES / RANGETOPS			48” COMMERCIAL STYLE RANGES / RANGETOPS		
	KFDC500J	KFGC500J	KCGC500JSS	KFDC506J	KFGC506J	KCGC506JSS	KFDC558J	KFGC558J	KCGC558JSS
UNDER CABINET HOODS									
30” - **KVUB400GSS**	✓	✓	✓	×	×	×	×	×	×
36” - **KVUB406GSS**	×	×	×	×	×	×	×	×	×
30” - **KVUB600DSS**	✓	✓	✓	×	×	×	×	×	×
36” - **KVUB606DSS**	×	×	×	×	×	×	×	×	×
30” - **KXU2830JSS**	✓	✓	✓	×	×	×	×	×	×
36” - **KXU2836JSS**	×	×	×	×	×	×	×	×	×
WALL MOUNT AND ISLAND MOUNT HOODS									
30” - **KVWB400DSS**	✓	✓	✓	×	×	×	×	×	×
36” - **KVWB406DSS**	×	×	×	×	×	×	×	×	×
30” - **KVWB600HBS**	✓	✓	✓	×	×	×	×	×	×
36” - **KVWB606HBS**	×	×	×	×	×	×	×	×	×
36” - **KVIB606DSS**	×	×	×	×	×	×	×	×	×
DOWNDRAFT									
30” - **KXD4630YSS**	×	×	×	×	×	×	×	×	×
36” - **KXD4636YSS**	×	×	×	×	×	×	×	×	×
PRO STYLE VENTILATION AND LINERS									
30” - **KVUC600KSS**	✓	✓	✓	×	×	×	×	×	×
36” - **KVUC606KSS**	×	×	×	✓	✓	✓	×	×	×
36” - **KVWC906KSS**	×	×	×	✓	✓	✓	×	×	×
48” - **KVWC908KSS**	×	×	×	×	×	×	✓	✓	✓
36” - **KVWC956KSS**	×	×	×	✓	✓	✓	×	×	×
48” - **KVWC958KSS**	×	×	×	×	×	×	✓	✓	✓
30” - **UVL5430JSS**	✓	✓	✓	×	×	×	×	×	×
36” - **UVL6036JSS***	×	×	×	✓	✓	✓	×	×	×
48” - **UVL6048JSS***	×	×	×	×	×	×	✓	✓	✓

*** Custom hood liners paired with commercial style ranges and rangetops must be used with blower**: UXB1170KYS (1,170 CFM)

**** Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer’s responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

IMPORTANT: Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

KitchenAid®

GAS COOKTOP AND VENTILATION PAIRING GUIDE

GAS COOKTOPS

	30” GAS COOKTOPS				36” GAS COOKTOPS		
	KCGS550ESS	KCGS950ESS	KCGD500GSS	KCGD500GSS	KCGS550ESS	KCGS950ESS	KCGD500GSS
UNDER CABINET HOODS							
30” - **KVUB400GSS**	✓	✓	✓	✓	×	×	×
36” - **KVUB406GSS**	×	×	×	×	✓	✓	✓
30” - **KVUB600DSS**	✓	✓	✓	✓	×	×	×
36” - **KVUB606DSS**	×	×	×	×	✓	✓	✓
30” - **KXU2830JSS**	✓	✓	✓	✓	×	×	×
36” - **KXU2836JSS**	×	×	×	×	✓	✓	✓
WALL MOUNT AND ISLAND MOUNT HOODS							
30” - **KVWB400DSS**	✓	✓	✓	✓	×	×	×
36” - **KVWB406DSS**	×	×	×	×	✓	✓	✓
30” - **KVWB600HBS**	✓	✓	✓	✓	×	×	×
36” - **KVWB606HBS**	×	×	×	×	✓	✓	✓
36” - **KVIB606DSS**	×	×	×	×	✓	✓	✓
DOWNDRAFT							
30” - **KXD4630YSS**	✓	✓	✓	✓	×	×	×
36” - **KXD4636YSS**	×	×	×	×	✓	✓	✓
PRO STYLE VENTILATION AND LINERS							
30” - **KVUC600KSS**	✓	✓	✓	✓	×	×	×
36” - **KVUC606KSS**	×	×	×	×	✓	✓	✓
36” - **KVWC906KSS**	×	×	×	×	✓	✓	✓
48” - **KVWC908KSS**	×	×	×	×	×	×	×
36” - **KVWC956KSS**	×	×	×	×	✓	✓	✓
48” - **KVWC958KSS**	×	×	×	×	×	×	×
30” - **UVL5430JSS***	✓	✓	✓	✓	×	×	×
36” - **UVL6036JSS***	×	×	×	×	✓	✓	✓
48” - **UVL6048JSS***	×	×	×	×	×	×	×

*** Custom hood liners can be used with any of the following blower motors:**
UXB1170KYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0585KYS (585 CFM)

**** Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer’s responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

IMPORTANT: Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

KitchenAid®

ELECTRIC COOKTOP AND VENTILATION PAIRING GUIDE

ELECTRIC COOKTOPS

	30” ELECTRIC COOKTOPS		30” INDUCTION COOKTOPS		36” ELECTRIC COOKTOPS		36” INDUCTION COOKTOPS
	KCES550H	KCED600G	KICU500X	KICU509X	KCES556H	KCED606G	KICU569X
UNDER CABINET HOODS							
30” - **KVUB400GSS**	✓	✓	✓	✓	×	×	×
36” - **KVUB406GSS**	×	×	×	×	✓	✓	✓
30” - **KVUB600DSS**	✓	✓	✓	✓	×	×	×
36” - **KVUB606DSS**	×	×	×	×	✓	✓	✓
30” - **KXU2830JSS**	✓	✓	✓	✓	×	×	×
36” - **KXU2836JSS**	×	×	×	×	✓	✓	✓
WALL MOUNT AND ISLAND MOUNT HOODS							
30” - **KVWB400DSS**	✓	✓	✓	✓	×	×	×
36” - **KVWB406DSS**	×	×	×	×	✓	✓	✓
30” - **KVWB600HBS**	✓	✓	✓	✓	×	×	×
36” - **KVWB606HBS**	×	×	×	×	✓	✓	✓
36” - **KVIB606DSS**	×	×	×	×	✓	✓	✓
DOWNDRAFT							
30” - **KXD4630YSS**	✓	✓	✓	✓	×	×	×
36” - **KXD4636YSS**	×	×	×	×	✓	✓	✓
PRO STYLE VENTILATION AND LINERS							
30” - **KVUC600KSS**	✓	✓	✓	✓	×	×	×
36” - **KVUC606KSS**	×	×	×	×	✓	✓	✓
36” - **KVWC906KSS**	×	×	×	×	✓	✓	✓
48” - **KVWC908KSS**	×	×	×	×	×	×	×
36” - **KVWC956KSS**	×	×	×	×	✓	✓	✓
48” - **KVWC958KSS**	×	×	×	×	×	×	×
30” - **UVL5430JSS**	✓	✓	✓	✓	×	×	×
36” - **UVL6036JSS***	×	×	×	×	✓	✓	✓
48” - **UVL6048JSS***	×	×	×	×	×	×	×

*** Custom hood liners can be used with any of the following blower motors:**
UXB1170KYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0585KYS (585 CFM)

**** Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer’s responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

IMPORTANT: Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.