AL55OSCSSIFLHD



31.63" x 23.5" x 23.38" (H x W x D)

Built-in undercounter ADA-compliant all-refrigerator for outdoor use featuring a panel-ready door, stainless steel cabinet, lock, and digital controls

Highlights:

Weatherproof design makes unit durable for safe installation in outdoor kitchens

32" height allows easy installation under lower ADA-compliant counters

Panel-ready door lets you customize the unit for a seamless look that integrates into your kitchen

Product Features:

24" Wide Outdoor All-Refrigerator	Made with a 24" footprint that offers full storage capacity in a uniquely slim fit and an ADA-compliant height
ADA-compliant	32” height allows for installation within ADA-compliant spaces
Panel-ready door	Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the refrigerator door or blend it into your cabinetry design; panel size: 23 3/16" W x 27 3/4" H and at least 3/4" thick; 10 lbs. maximum; customers provide their own handles
Commercially approved	ETL-S listed to NSF-7 commercial standards
Weatherproof design	Durable construction for safe installation in outdoor kitchens
Built-In capable	Front-breathing design allows the unit to be built-in under counters
Digital control panel	Makes for easy temperature reading/management with electronic controls inside
Factory installed lock	Keyed lock for secure interior
Stainless steel exterior	Durable construction with a stylish look

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**

SUMMIT

AL55OSCSSIFLHD Specifications:

Overview	
Height of Cabinet	31.63" (80 cm)
Width	23.5" (60 cm)
Depth	23.38" (59 cm)
Depth with Panel	24.13" (61 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	4.2 cu.ft. (119 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	250.0kWh/year
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	95.0 lbs. (43 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101149417
Refrigerator Features	
Door Swing	LHD
Reversible	No
Shelf Type	Glass
Shelf Qty	3
Full Door Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant Type	R600a
Refrigerant Amount	1.23oz.
High Side PSI	150.0
Low Side PSI	50.0
Level Legs Qty	4
Interior Light	Yes
Temperature Range	36 to 46ºF
Sound Level	33.2 dB
Dimensions	

Interior Height	23.5" (60 cm)
Interior Width	19.0" (48 cm)
Interior Depth	16.0" (41 cm)
Compressor Step Height	5.5" (14 cm)
Compressor Step Width	19.0" (48 cm)
Compressor Step Depth	5.0" (13 cm)



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**