PTS9000BN/SN

GE Profile™ 30" Smart Built-In Convection Single Wall Oven with In-Oven Camera and Air Fry

DIMENSIONS AND INSTALLATION INFORMATION

NOTE: Single wall ovens are NOT approved for stacking above or below another single wall oven.


NOTE: Wall coverings, countertops and cabinets surrounding the wall oven must be able to withstand a temperature of up to 200°F (94°C).


NOTE: If the cabinet in which the wall oven is installed does not have a solid bottom, two braces or runners must be installed to support the weight of the oven. The runners and braces must support up to 220 lbs (99 kg).

NOTE: Door handle protrudes 3" from door face. Cabinets and drawers on adjacent 45° and 90° walls should be placed to avoid interference with the handle.


ATTENTION INSTALLER: Electric wall ovens are NOT approved for installation with a plug and receptacle. They must be hard wired into an approved junction box.

IMPORTANT: Before installing, consult installation instructions packed with product for current dimensional data.





Dimension and installation information are shown in inches.



KW RATING	
240V	4.5
208V	3.4
BREAKER SIZE	
240V	20 Amps
208V	20 Amps

	PTS9000
Cabinet	**30"**
A - Overlap of oven at top of cutout	**1"**
B - Overlap of oven other side of edge of cutout	**3/4"**
C - Overlap of oven at bottom of cutout	**1-1/4"**
Oven	
D - Install depth	**23-1/2"**
E - Overall height with trim	**28-5/8"**
F - Overall width	**29-3/4"**

GE APPLIANCES

For answers to your Monogram, GE Café™, GE Profile™ or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service, 800.626.2000.

GE APPLIANCES FIT GUARANTEE

ADA COMPLIANT

UL® Listed by Underwriters Laboratories

K

Specification Revised 10/20

PTS9000BN/SN

GE Profile™ 30" Smart Built-In Convection Single Wall Oven with In-Oven Camera and Air Fry


OPTIONAL UNDERCOUNTER DIMENSIONS AND INSTALLATION INFORMATION

NOTE: 30" Single electric wall ovens are approved for installation below a countertop, and below certain gas and electric cooktops. Refer to the Approved Combinations Matrix available at geappliances.com for specific information.


NOTE: 30" Single electric wall ovens are approved for installation above 27" and 30" warming drawers.

ATTENTION INSTALLER: Electric wall ovens are NOT approved for installation with a plug and receptacle. They must be hard wired into an approved junction box.

IMPORTANT: Before installing, consult installation instructions packed with ALL products for current dimensional and combination data.




SIDE-BY-SIDE INSTALLATION (TWO OVENS IN SEPARATE CUTOUTS)



NOTE: One cooktop may be centered over either oven in the side-by-side installation.

INSTALLATION BELOW A COOKTOP

IMPORTANT: Maintain a minimum distance of **31 1/4"** from the top surface of the countertop to the wall oven platform to ensure that the cooktop and wall oven do not interfere with each other (see picture).



GE APPLIANCES

For answers to your Monogram, GE Café™, GE Profile™ or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service, 800.626.2000.

PTS9000BN/SN

GE Profile™ 30" Smart Built-In Convection Single Wall Oven with In-Oven Camera and Air Fry

FEATURES AND BENEFITS

In-oven camera

No preheat air fry

Anywhere control with remote notifications

Remote temperature probe

Dehydrate mode

Precision cooking modes

True European Convection with Direct Air

No preheat options

Brilliant touch 7" display

Soft-close door

Never-scrub, heavy-duty smooth glide roller racks

Self-clean oven with optional Steam Clean


10-pass hidden bake element

10-pass dual-broil element

Fit Guarantee

Model PTS9000BNTS – Black Stainless

Model PTS9000BNTS – Stainless Steel



GUARANTEED FIT

Replacing a similar wall oven from GE Appliances or another brand? GE wall ovens are guaranteed for an exact fit or GE Appliances will pay up to $300 toward modifications.

Visit geappliances.com for more info

GE APPLIANCES

Specification Revised 10/20