# PVM9225SR/RY

## *GE Profile™ 2.2 Cu. Ft. Over-the-Range Sensor Microwave Oven*

### DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)


**NOTE:** Requires 120V grounded outlet. Electrical receptacle must be located in cabinet above microwave oven. No additional wiring, venting or cabinet rebuilding necessary in many cases. Complete detailed, easy-to-follow installation instructions and convenient full-size templates are packed with the microwave oven.

**IMPORTANT INFORMATION:** When installing the microwave oven over a range, allow minimum of 2" from bottom of microwave oven to top of range backguard to allow for removal of light covers.

**VENTILATION OPTIONS:** The microwave ovens are designed for adaptation to the following three types of ventilation:

-Outside exhaust (vertical – as shown)
-Outside exhaust (horizontal)
-Recirculating (non-vented ductless – see Filter Kit drawing)

**INSTALLATION INFORMATION:** This information is not intended to be used for installing unit described. Before installing, consult installation instructions packed with product/kit for current dimensional data.




GE APPLIANCES

*For answers to your Monogram, Café,™ GE Profile™ or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service, 800.626.2000.*

AHAM VERIFIDE

UL Listed by Underwriters Laboratories

Specification Revised 12/21

# PVM9225SR/RY

## *GE Profile™ 2.2 Cu. Ft. Over-the-Range Sensor Microwave Oven*

### DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

### DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

**HOOD EXHAUST DUCT:** Outside ventilation requires a HOOD EXHAUST DUCT. Read the following carefully.

**EXHAUST CONNECTION:** The hood exhaust has been designed to mate with a standard 3-1/4" x 10" rectangular duct. If a round duct is required, a rectangular-to-round transition adaptor must be used. Do not use less than a 6" diameter duct.

**REAR EXHAUST:** If a rear or horizontal exhaust is to be used, care should be taken to align exhaust with space between studs, or wall should be prepared at the time it is constructed by leaving enough space between the wall studs to accommodate exhaust.

**MAXIMUM DUCT LENGTH:** For satisfactory air movement, the total duct length of 3-1/4" x 10" rectangular or 6" diameter round duct should not exceed 140 equivalent feet.


**ELBOWS, TRANSITIONS, WALL AND ROOF CAPS,** etc., present additional resistance to airflow and are equivalent to a section of straight duct which is longer than their actual physical size. When calculating the total duct length, add the equivalent length of all transitions and adaptors plus the lengths of all straight duct sections. The chart below shows the approximate feet of equivalent length of some typical ducts.

| DUCT | EQUIVALENT FEET |
|---|---|
| **A.** Rectangular-To-round Transition Adaptor | 5 ft. |
| **B.** Wall Cap | 40 ft. |
| **C.** 90° Elbow | 10 ft. |
| **D.** 45° Elbow | 5 ft. |
| **E.** 90° Elbow | 25 ft. |
| **F.** 45° Elbow | 5 ft. |
| **G.** Roof Cap | 24 ft. |


### OPTIONAL ACCESSORIES

Filler Panel Kits JX36BSS

When replacing a 36" range hood, this kit fills in the additional width to provide a custom built-in appearance. For installation between cabinets only; not for end-of-cabinet installation. Each kit contains two 3"-wide filler panels.



Filter Kit WB02X35607 (included) Recirculating Charcoal Filter Kit To be used when the microwave oven cannot be vented to the outside.




GE APPLIANCES


Specification Revised 12/21

# PVM9225SR/RY

## *GE Profile™ 2.2 Cu. Ft. Over-the-Range Sensor Microwave Oven*

### DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

### FEATURES AND BENEFITS




Extendable vent – Extend the built-in vent for additional cooktop ventilation that doubles the capture rate of typical over-the-range microwaves for smoke and odors.

Sensor Cooking Controls – Microwave sensor cooking automatically adjusts time and heating power to optimize results.

2.2 cu. ft. Capacity – This large capacity microwave gives you all the space you need to cook and reheat your favorites.

400 CFM Range Hood – Quickly remove smoke, steam and odors with a powerful ventilation hood that has four speeds.

Chef Connect – Sync your clocks and range elements with the smart microwave's surface light and vent.

Steam Clean – A steam cleaning mode makes it easy to clean spills and stuck-on food in no time.

LED Cooktop Lighting – Illuminate your cooking surface with bright over-the-stove lighting that saves energy and reduces maintenance costs.

Model PVM9225SRSS - Stainless Steel

Model PVM9225RYSS - Stainless Steel with black accents

GE APPLIANCES

Specification Revised 12/21