PUSH-TO-START

COMMERCIAL STACK DRYER

Built for Reliable Performance

Speed Queen's stack dryer offers the same great features as the single load dryer. Two commercial dryers in the space of one, both operating independently, including independent controls for optimum usage. They're designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. Our cabinet design maintains the perfect balance of heat, airflow and tumble action for optimal performance and efficiency. The equipment provides an advantage on such issues as energy conservation, equipment breakdowns and vandalism. The dry cycle is efficient and fast. Customers have the flexibility to choose from four heat/cycle selections. Bottom dryer is ADA compliant.

- Industry's largest door opening 2.06 sq. ft. (1914 cm²)
- Quiet, efficient blower system
- Door is reversible for installation flexibility
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)
- 100% serviceable from the front
- Space-saving narrow cabinet 26.875" (683 mm)
- Upfront lint filter easy to clean and secured
- Durable galvanized steel cylinder





Push-to-Start control provides easy to start activation indicated by "In Use" light.


Speed Queen

SPECIFICATIONS

COMMERCIAL STACK DRYER

MODEL - see below for all models and activation available		
CONTROL OPTION		Push-to-Start
COLOR		White
CAPACITY - lb (kg)		18 (8.2) (ea)
OVERALL WIDTH - in (mm)		26.875 (683)
OVERALL DEPTH - in (mm)		28 (711)
OVERALL HEIGHT - in (mm)		78.17 (1986)
CYLINDER VOLUME - cu. ft. (liters)		7.0 (198) (ea)
MOTOR (CAPACITOR START AND THERMAL PROTECTED)		.33 HP
TYPE OF GAS (GAS MODELS ONLY)		Factory equipped natural/ mixed gas
AIR OUTLET DIAMETER - in (mm)		4 (102)
EXHAUST AIRFLOW - cfm (liters/sec)		220 (105)
CYCLE TEMPERATURE		Normal, Perm Press Delicate, No Heat
ELECTRICAL REQUIREMENTS	▪ Electric	120/240/60/1-30 amp 120/208/240/60/1-30 amp
	Gas	120/60/1-15 amp
HEATING ELEMENT	Electric	5350W, 240V 4750W, 208V
	Gas	25,000 Btu
NET WEIGHT - lb (kg)	Electric	262 (119)
	Gas	262 (119)
SHIPPING WEIGHT lb (kg)	Electric	272 (123.4)
	Gas	272 (123.4)
SHIPPING DIMENSIONS APPROX. - in (mm)	Width	33 (838)
	Depth	30 (762)
	Height	80 (2032)
AGENCY APPROVALS	Electric	cULus
	Gas	cCSAus

MODELS	VOLTAGE/FREQ/PH		ACTIVATION
SSEMNAGS173TW01	120/240/60/1	Electric	Push-to-Start
SSEMNAGS151TW01	120/208/60/1		
SSGMNAGS111TW01	120/60/1	Gas	



A.	OVERALL WIDTH - in (mm)	26.875 (683)
B.	OVERALL DEPTH - in (mm)	28 (711)
C.	OVERALL HEIGHT - in (mm)	78.17 (1986)
D.	FLOOR TO DOOR OPENING -in (mm)	15.44 (392)
E.	DOOR SWING - in (mm)	23.5 (597)

▪ Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

©2016 Alliance Laundry Systems LLC AM16-0080