ZLINE 36 in. Wooden Wall Mount Range Hood in Shiplap Bright White Finish (KPWW-36)



INTRODUCTION

Luxury isn't meant to be left desired—it's meant to be attainable. The ZLINE 36 in. Wooden Wall Mount Range Hood in Shiplap Bright White Finish (KPWW-36) provides a professional culinary experience by pairing built-to-last quality with a timeless style. Achieve ZLINE Attainable Luxury® excellence with unrivaled performance designed to enhance your kitchen's capability.

FEATURES & BENEFITS

4-Speed Fan Control - Choose the appropriate air flow among 120/240/320/400 CFM for your cooking situation

Convertible Range Hood - This unit can be externally vented or recirculated (ductless) when paired with specialty crown molding (not included, SKU no. CM6V-KBWW) to reduce harmful odors

Powerful Ventilation - The highest speed setting of 400 CFM air flow efficiently moves large amounts of air away from your cooking area

Easy Installation - ZLINE range hoods are designed to fit standard (circular) ductwork for simple installation

Safety First - ZLINE range hood handles are for cosmetic purposes only and should not be used for hanging items

Warranty - ZLINE range hoods carry a 3-year parts-only warranty, in addition to a lifetime motor warranty

SPECIFICATIONS OVERVIEW

GENERAL PROPERTIES

SKU	KPWW-36
Finish	Wood/White
# of Lights	2
Airflow	120/240/320/400
Duct Size	6
Outdoor Approved	No

LIMITED WARRANTY

Warranty	3 year parts, life-time motor warranty

DIMENSIONS

Product Dimensions (in.)	36 in. W 19.75 in. D 13.25 in. H

POWER / RATINGS

Amps	3.5
Voltage	110

CERTIFICATIONS

ETL Listed,CEC Listed

ZLINE 36 in. Wooden Wall Mount Range Hood in Shiplap Bright White Finish (KPWW-36)



SPECIFICATIONS IN-DEPTH

GENERAL PROPERTIES

SKU	KPWW-36
Finish	Wood/White
# of Lights	2
# of Speeds	4
Airflow	120/240/320/400
Duct Size (in.)	6
Max CFM	400
Outdoor Approved	No
Recirculating	No
Remote Blower	No

LIMITED WARRANTY

Warranty	3 year parts, life-time motor warranty

DIMENSIONS

Product Dimensions (in.)	36 in. W 19.75 in. D 13.25 in. H

POWER / RATINGS

Amps	3.5
Voltage	110

CERTIFICATIONS

ETL Listed,CEC Listed