36" Industrial Style Induction Range

800 Series – Stainless Steel HIS8657U



HIS8657U
Stainless Steel

The 36" 5 element industrial-style induction range delivers power and performance in a commercial-inspired design.

Features & Benefits

- CombiZone lets you combine two cooking zones into one large zone for longer pans and grills.
- Frameless, edge-to-edge surface glass cooktop for a sleek, streamlined look.
- Convection Multi-Rack combines a third heating element with a back fan for even browning and time savings by using multiple racks at one time.
- A full extension telescopic rack rail offers easy access to the oven cavity.
- Dampened hinges softly guide the QuietClose® door shut so the oven door never slams.
- Easy to view, ergonomic tilted display.
- Induction cooking is faster and more efficient than gas or electric.
- Best-in-class 5.5 kW element for maximum power.

General Properties	
Cooking modes	Broil, Air fry, Convection broil, Convection roast, Pizza, Proof, Multi rack, Convection bake, Bake
Cleaning type	Catalytic cleaning / Steam assist
Type of surface	Ceramic Glass
Knob material	Plastic
Interior light	2
Kitchen timer	Yes
Oven Performance	
Bake / broil element watts	1,700 / 1,700 W
Convection element watts	2 x 1,550 W
Burner Performance	
Total induction elements	5
Power of back left element watts	1,850 W (3,000 w/ boost)
Power of front left element watts	1,850 W (3,000 w/ boost)
Power of front right element watts	2,300 W (3,700 w/ boost)
Power of back right element watts	1,400 W (2,200 w/ boost)
Power of center element watts left (1 generator)	1,850/2,600 W (3,000/5,500 w/ boost)

Technical Details	
Watts	8,400 W
Circuit breaker	40 A (50 A recommended)
Volts	208V / 240V
Frequency	60 Hz
Plug type / Cord length	Fixed connection (no cord)
Energy source	Electric
Dimensions & Weight	
Overall appliance dimensions (HxWxD)	36" x 35 15/16" x 24 51/64" (w/ bull nose 26 19/64")
Required cutout size (HxWxD)	36" x 36" x 25"
Adjustable range height	35 3/4" Min. 36 3/4" Max.
Oven cavity size	5.4 cu. ft.
Overall oven interior dimensions (HxWxD)	15.04" x 28.46" x 17.72"
Usable oven interior dimensions (HxWxD)	14.57" x 26.97" x 16.14"
Net weight	215 lbs

Accessories–Included

Use and care manual, installation guide, temperature probe, 2 standard racks, 1 telescopic rail, anti-tip protection kit

Intertek

† To be fully ADA compliant, these units must be installed according to ADA guidelines. Please check current ADA requirements for guidance on installation.

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

36" Industrial Style Induction Range

800 Series – Stainless Steel HIS8657U

Accessories–Optional

IMAGE TO COME

12029918
Spare Part NB

IMAGE TO COME

11068084
Spare Part NB

IMAGE NOT FINAL



HEZ90T36UC
36" Range Toe Kick
Stainless Steel


IMAGE NOT FINAL




HEZ9LMUC
Metal Pedestal Feet,
Set of 4
Stainless Steel

Installation Details


Measurements in inches (mm)



Measurements in inches (mm)



Cabinet clearance requirements



The distance that must be maintained when installing the range shall be:

A: Max. 7″ (178 mm)
B: Min. 18″ (457 mm)
C: Min. 30″ (762 mm) clearance between the top of the cooking surface and the bottom of the ventilation hood or a non-combustible wall cabinet

D: Min. 30″ (762 mm)
Min. 36″ (914 mm)
E: Min. 25″ (635 mm)
F: Max. 13″ (330 mm)
G: Min. 30″ (762 mm)
Min. 36″ (914 mm)
Zero clearance between adjacent combustible structure below the countertop surface and sides of the appliance

H: 35 3/8″–36 5/8″(898–930 mm)
I: Max. 11″ (279 mm)
J: Max. 7″ (178 mm)

X: Grounded outlet

From cooking surface to side materials: no clearance is required from unit walls to adjacent vertical combustible walls on rear, right or left

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.