36" Industrial Style Dual Fuel Range

800 Series – Stainless Steel HDS8657U



HDS8657U
Stainless Steel

36" Bosch range with six burners offering more flexibility in the way you cook.

Features & Benefits

- Powerful 20,000 BTU double ring burner speeds cooking time.
- Convection Pro combines a third heating element with a back fan for even browning and time savings by using multiple racks at one time.
- Dishwasher safe grates for easy cleaning.
- A full extension telescopic rack rail offers easy access to the oven cavity.
- Dampened hinges softly guide the QuietClose® door shut so the oven door never slams.
- Illuminated knobs indicates when the burner is on, enhancing safety and monitoring .

General Properties	
Cooking modes	Broil, Air fry, Convection broil, Convection roast, Pizza, Proof, Multi rack, Convection bake, Bake
Cleaning type	Catalytic clean coating, Steam assist cleaning
Type of grate	Cast iron
Knob material	Plastic
Interior light	2
Kitchen timer	Yes
Sealed burners	Yes
Oven Performance	
Bake / broil element watts	1,700 / 1,700 W
Convection element watts	2x 1,550 W
Burner Performance	
Total cooktop burners	6
Total cooktop (NG / LP) BTU	73,000 / 71,000
Power of front left burner (NG / LP) BTU	20,000 / 18,000
Power of back left burner (NG / LP) BTU	5,000 (OptiSim) / 5,000
Power of back center burner (NG / LP) BTU	12,000 / 12,000
Power of front center burner (NG / LP) BTU	12,000 / 12,000
Power of back right burner (NG / LP) BTU	12,000 / 12,000
Power of front right burner (NG / LP) BTU	12,000 / 12,000

Technical Details	
Circuit breaker	20 A
Volts	208V / 240V
Frequency	60 Hz
Plug type / Cord length	Fixed connection (no cord)
Energy source	Mixed Electric / Gas
Gas type	Natural gas 14.9 mbar (USA) [7" WC]
Alternative gas type	LP 27.4 mbar (USA) [11" WC]
Dimensions & Weight	
Overall appliance dimensions (HxWxD)	36" x 35 15/16" x 24 49/64" (w/ bull nose 26 17/64")
Required cutout size (HxWxD)	36" x 36" x 25"
Adjustable range height	35 9/16" Min. 36 5/8" Max.
Oven cavity size	5.4 cu. ft.
Overall oven interior dimensions (HxWxD)	15.04" x 28.46" x 17.72"
Usable oven interior dimensions (HxWxD)	14.57" x 26.97" x 16.14"
Appliance Net weight	216 lbs

Accessories—Included

Use and care manual, installation guide, temperature probe, LP conversion kit, 2 standard racks, 1 telescopic rail, anti-tip protection kit

Intertek

† To be fully ADA compliant, these units must be installed according to ADA guidelines. Please check current ADA requirements for guidance on installation.

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

36" Industrial Style Dual Fuel Range

800 Series – Stainless Steel HDS8657U

Accessories–Optional

IMAGE TO COME

12029918
Spare Part NB

IMAGE TO COME

11068084
Spare Part NB

IMAGE NOT FINAL



HEZ90T36UC
36" Range Toe Kick
Stainless Steel

IMAGE NOT FINAL



HEZ90H36UC
36" Rear Vent Trim
Extension
Stainless Steel

IMAGE NOT FINAL



HEZ90K36UC
36" Low Backguard
Stainless Steel


IMAGE NOT FINAL




HEZ9LMUC
Metal Pedestal Feet,
Set of 4
Stainless Steel

Installation Details


Measurements in inches (mm)



Measurements in inches (mm)



Cabinet clearance requirements



The distance that must be maintained when installing the range shall be:

B: Min. 18″ (457 mm)
C: Min. 30″ (762 mm) clearance between the top of the cooking surface and the bottom of the ventilation hood or a non-combustible wall cabinet

Min. 36″ (914 mm) clearance between the top of the cooking surface and the bottom of a combustible wall cabinet

D: Min. 30″ (762 mm)
Min. 36″ (914 mm)
E: Min. 25″ (635 mm)
F: Max. 13″ (330 mm)
G: Min. 30″ (762 mm)
Min. 36″ (914 mm)
Zero clearance between adjacent combustible structure below the countertop surface and sides of the appliance

H: 35 3/8″–36 5/8″(898–930 mm)
I: Max. 11″ (279 mm)
J: Max. 7″ (178 mm)
K: Max. 6″ (150 mm)
L: Max. 11″ (279 mm)

X: Grounded outlet
Y: Gas supply line

From cooking surface to side materials: no clearance is required from unit walls to adjacent vertical combustible walls on rear, right or left

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.