
avanti®









AVDWP18W0W | AVDWP18W1B | AVDWP18W3S

Avanti 18” ADA Built-In Dishwasher

Compact cleaning performance for smaller kitchens. This ADA-compliant 18-inch built-in dishwasher accommodates up to 8 place settings while operating at a quiet 49 dBA. A 3-level wash system, Smart Clean cycle and hard food disposer with 3-stage filtration help deliver dependable everyday cleaning.

- ADA-Compliant Low-Profile Installation
- 3-Level Wash System
- Smart Clean Sensor Cycle
- Hard Food Disposer + 3-Stage Filtration
- NSF-Certified Sanitize Option
- 49 dBA Quiet Operation
- 1 Year Limited Warranty

Specifications

Sound Level: 49 dBA
Assembled Dims: 17.55" x 22.6" x 32.56" (W x D x H)
Assembled Wgt: 70.55 lbs
Shipping Dims: 20.55" x 26.26" x 34.92" (W x D x H)
Shipping Wgt: 84.9 lbs
Depth - Door Open at 90°: 45.87"
Capacity: 8 Place Settings
Required Cutout: 18” W x 24” D x 32.5”–34.75” H”
Electrical Specifications: 8.9A/120V/60Hz
Power Connection: Hardwire or Approved Power Cord Kit





avantiproducts.com

Certifications

The Legacy Companies
Weston, FL 33331 U.S.A.

(954) 567-4500 - U.S.A.
(438) 800-4777 - Canada

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this document are subject to change without notice. While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.

© 2026 The Legacy Companies, LLC. All Rights Reserved.

INSTALLATION PREPARATION

PREPARE DISHWASHER ENCLOSURE

- The dishwasher must be installed so that drain hose is no more than 12' in length for proper drainage.
- The dishwasher must be fully enclosed on the top, sides and back, and must not support any part of the enclosure.

CLEARANCES:

- When installed into a corner, allow 2" min. clearance between dishwasher and adjacent cabinet, wall or other appliances. Allow 23-1/8" min. clearance from the front of the dishwasher for door opening.

⚠ WARNING

To reduce the risk of electric shock, fire, or injury to persons, the installer must ensure that the dishwasher is completely enclosed at the time of installation.

